

Olympus® P-400 Printer



LECO is proud to announce the arrival of the **Olympus® P-400 High Speed Photo-Quality Printer**. The P-400 provides continuous-tone, dye-sublimation printing for photo-quality results.

Simply connect the P-400 to your PC or Mac* via USB port or parallel port (Windows®-based systems without USB port) for convenient viewing and printing directly from your computer. Or print DCF, JFIF/JPEG, or TIF photos taken with your digital camera using the printer's SmartMedia Card slot.

The P-400's convenient LCD Information Display Panel allows you to easily view images and select the ones you want to print. Choose the size of the print, as well as the number of copies. Various print size options include full-size image, single-sheet photo album, postcard, and index sheet (with up to 260 pictures). Print up to 50 copies at a time using one-print selection.

- **True, continuous-tone dye-sublimation technology**
- **16.7 million colors (8 bit/color)**
- **Clear laminate layer helps protect your prints**
- **Full-color, B&W, and sepia filters**
- **LCD panel for checking and selecting images**

861-336 P-400 Package

- Paper Trial Pack (5 sheets, A4 size—11.6 in. x 8.25 in. [297 mm x 210 mm])
- Ink Ribbon Trial Pack (for 5 prints)
- CD-ROM (driver, software, utility software)
- Paper tray, output tray, AC power cord
- Manual, Warranty

For professional users who require minimum downtime and the utmost in dependability, we recommend the P-400 Business Edition Package. This complete photo printing solution combines the printer with supplies and services designed to promote uninterrupted output capability and maximum productivity in a fast-paced business environment.

861-337 P-400 Business Edition Package

- Consumables to print 150 full-size sheets
- One-Year Priority Exchange Service Program
- Toll-free technical support for printing problems, replacement, or loaner unit if necessary via overnight delivery {there will be an additional charge for the loaner unit}.
- CD-ROM (driver, software, utility software)
- Paper tray, output tray, AC power cord
- Manual, Warranty

* Your computer system must be USB-compatible.

Specifications

Resolution	314 dpi
Head Dots	2400 dots
Paper Supply Method	Cut paper, cassette method (50 sheet capacity)
Ink Ribbon	Refill cassette type (50-frame capacity)
Output Tray	50 sheet capacity
Print Colors	3 colors (Y+M+C) and overcoat layer
Paper Types	<ul style="list-style-type: none">• A4 size standard paper 8.3 in. x 11.7 in. (210 mm x 297 mm)• A5 wide standard paper 7.9 in. x 8.3 in. (200 mm x 210 mm)• L-size card paper (four 3.5 in. x 4.7 in. [89 mm x 119 mm] sheetson A4 size)• Postcard paper (two 3.9 in. x 5.8 in. [100 mm x 148 mm] sheets on A4 size)
Printing Size	<ul style="list-style-type: none">• A4—7.6 in. x 10.2 in. (194 mm x 258 mm)• A5—7.6 in. x 6.4 in. (194 mm x 162 mm)
Printing Speed	Maximum size A4 picture, 2.5 minutes (does not include data transfer and picture process time)
Printing Via	Parallel Port, USB, SmartMedia, PC card, CompactFlash, Memory Stick, or direct from PC
Card Input	<ul style="list-style-type: none">• Smart Media 3V (3.3V) 4, 8, 16, 32, 64 MB (Smart Media 5V compatible with PC card adapter MA-2...sold separately)• PCMCIA (memory card) Type II
Picture Layout	<ul style="list-style-type: none">• Full Size—7.6 in. x 10.2 in. (194 mm x 258 mm), from 1 to 16 images/pg.• Card: 2 to 4 postcards/pg.• Photo-Album: from 1 to 6 images/pg. with bkgd.• Index: 45 to 260 images/pg.
Print Options	Stamp, Background, Frame, Filter, Date & Time, Rotation, Trimming
Compatible Graphics File Formats	DCF compatible, JFIF, EXIF compatible (JPEG, TIFF), DPOF compatible (image scheduling, number setting, trimming setting)
Image Display LCD	Monochrome 16 gradations, 1.3 in. x 1.3 in. (32 mm x 32 mm)
PC Interface	<ul style="list-style-type: none">• IEEE1284 (parallel port) Windows 95/98, NT4.0, 2000 (Pentium or above, local PC only)• USB Windows 98, 2000 (Pentium or above, local PC only) Macintosh OS8.6/OS9 (New G3, iMac, iBook)
Power Source	110/120 V~, 50/60 Hz
Rated Power Consumption	180W
External Dimensions**	16.6 in. W x 12.3 in. H x 10.8 in. D (422 mm W x 311 mm H x 275 mm D) **does not include largest protrusion
Weight	25 lb. (11.3 kg)

V~ denotes VAC.

Specifications and part numbers may change. Consult LECO for latest information.

World Headquarters/United States

In United States (800) 292-6141
Outside U.S.A. (269) 983-5531

Spectroscopy Group

United States (Michigan) (269) 985-5496
For outside U.S.A., call nearest office listed below.

International Offices/Subsidiaries

Africa • LECO Africa (Pty.) Ltd.
Kempton Park, South Africa
Ph: 27-11-974-1681 • Fax: 27-11-974-1848

Argentina • LECO Argentina S.A.
Buenos Aires, Argentina
Ph: 54-114571-4651 • Fax: 54-11-4573-2722

Australia • LECO Australia Pty. Ltd.
Castle Hill, NSW, Australia
Ph: 61-2-9894-5955 • Fax: 61-2-9894-5247

Brazil • LECO Instrumentos Ltda.
Rio De Janeiro, Brazil
Ph: 5521-3461-9006 • Fax: 5521-2537-8575

Canada • LECO Instruments Ltd.
Mississauga, Ontario Canada
Ph: 905-564-6577 • Fax: 905-564-6582

China • LECO Corp/Beijing Office
Beijing, China
Ph: 86-10-6512-8877 • Fax: 86-10-6528-0373

Czech Republic • LECO Instrumente Plzen s.r.o.
Plzen/Czech Republic
Ph: 420-37-751-0811 • Fax: 420-37-725-9304

France • LECO France
GARGES-Les-GONESSE; Cedex, France
Ph: 33-1-34-45-46-00 • Fax: 33-1-39-86-41-05

Germany • LECO Instrumente GmbH
Mönchengladbach, Germany
Ph: 49-2166-687-0 • Fax: 49-2166-687-100

Hong Kong • LECO Instruments Hong Kong Ltd.
Kowloon, Hong Kong
Ph: 852-2387-7028 • Fax: 852-2708-4388

Italy • LECO Italy, S.R.L.
Milan, Italy
Ph: 39-02-953-43391 • Fax: 39-02-953-43461

Japan • Japan Analyst Corporation
Tokyo, Japan
Ph: 81 3(3493) 7281 • Fax: 81 3(5496) 7935

Korea • LECO Korea Co. Ltd.
Seoul, Korea
Ph: 822-562-4148 • Fax: 822-555-4135

Malaysia • LECO Instruments (M) Sdn. Bhd.
Selangor, D.E. Malaysia
Ph: 603-7805-2100 • Fax: 603-7805-2212

Mexico • LECO Mexico S.A. de C.V.
Monterrey, NL CP 64900 Mexico
Ph: 52-81-8349-3927 • Fax: 52-81-8349-6485

The Netherlands • LECO Europe B.V.
Geleen, The Netherlands
Ph: 31-46-4747473 • Fax: 31-46-4747333

Poland • LECO Polska Sp.z.o.o
Katowice, Poland
Ph: 48-32-2000-540 • Fax: 48-32-2000-536

Russia • Z.A.O. LECO Center Moscow
Moscow, Russia
Ph: 7095-710-3818 • Fax: 7095-710-3826

Spain • LECO Instrumentos S.A.
Madrid, Spain
Ph: 34-91-803-1250 • Fax: 34-91-804-0577

Sweden • LECO Corporation Svenska AB
Upplands Väsby, Sweden
Ph: 468-594-11000 • Fax: 468-594-11011

Taiwan • LECO Instruments Taiwan Ltd.
Taipei, Taiwan R.O.C.
Ph: 886-22-518-4699 • Fax: 886-22-518-4671

Thailand • LECO Instruments (Thailand) Ltd.
Bangkok, Thailand
Ph: 66-2-886-4350 • Fax: 66-2-886-4351

United Kingdom • LECO Instruments (U.K.) Ltd.
Stockport, Cheshire, England
Ph: 44-161-487-5900 • Fax: 44-161-456-0969

Venezuela • Instrumentos LECO Venezuela, C.A.
Caracas, Venezuela
Ph: 58-212-242-6836 • Fax: 58-212-241-8663